

TI Truck, Tractor & Trailer Schedule 1 – Truck, Tractor & Trailer – Approved December 2003

This schedule applies to trucks, tractors and trailers or combinations thereof exceeding a registered gross vehicle weight of 4 500 kg

<i>Defect(s) Needs Attention</i>	<i>Major Defect(s) Out of SERVICE</i>
1. Air Brake System • Audible air leak. • Slow air pressure build-up rate.	• Pushrod stroke of any brake exceeds the adjustment limit. • Air loss rate exceeds prescribed limit. • Inoperative towing vehicle (tractor) protection system. • Low air warning system fails or system is activated. • Inoperative service, parking or emergency brake.
2. Cab • Occupant compartment door fails to open.	• Any door fails to close securely
3. Cargo Securement • Insecure or improper load covering.	• Insecure cargo. • Absence, failure, malfunction or deterioration of required cargo securement device or load covering.
4. Coupling Devices • Coupler or mounting has loose or missing fastener.	• Coupler is insecure or movement exceeds prescribed limit. • Coupling or locking mechanism is damaged or fails to lock. • Defective, incorrect or missing safety chain/cable
5. Dangerous Goods	• Dangerous goods requirements not met.
6. Driver Controls • Accelerator pedal, clutch, gauges, audible and visual indicators or instruments fail to function properly	
7. Driver Seat • Seat is damaged or fails to remain in set position.	• Seatbelt or tether belt is insecure, missing or malfunctions.
8. Electric Brake System • Loose or insecure wiring or electrical connection.	• Inoperative breakaway device. • Inoperative brake.
9. Emergency Equipment & Safety Devices • Emergency equipment is missing, damaged or defective.	
10. Exhaust System • Exhaust leak.	• Leak that causes exhaust gas to enter the occupant compartment.
11. Frame and Cargo Body • Damaged frame or cargo body.	• Visibly shifted, cracked, collapsing or sagging frame member(s).
12. Fuel System • Missing fuel tank cap.	• Insecure fuel tank. • Dripping fuel leak.
13. General	• Serious damage or deterioration that is noticeable and may affect the vehicle's safe operation.
14. Glass and Mirrors • Required mirror or window glass fails to provide the required view to the driver as a result of being cracked, broken, damaged, missing or maladjusted.	• Required mirror or glass has broken or damaged attachments onto vehicle body.
15. Heater/Defroster • Control or system failure.	• Defroster fails to provide unobstructed view through the windshield.

<i>Defect(s) Needs Attention</i>	<i>Major Defect(s) Out of SERVICE</i>
16. Horn • Vehicle has no operative horn.	
17. Hydraulic Brake System • Brake fluid level is below indicated minimum level. • Parking brake is inoperative	• Brake boost or power assist is not operative. • Brake fluid leak. • Brake pedal fade or insufficient brake pedal reserve. • Activated (other than ABS) warning device. • Brake fluid reservoir is less than ¼ full.
18. Lamps and Reflectors • Required lamp does not function as intended. • Required reflector is missing or partially missing.	<i>When lamps are required:</i> • Failure of both low-beam headlamps. • Failure of both rearmost tail lamps. <i>At all times:</i> • Failure of a rearmost turn-indicator lamp. • Failure of both rearmost brake lamps.
19. Steering • Steering wheel lash (free-play) is greater than normal.	• Steering wheel is insecure, or does not respond normally. • Steering wheel lash (free-play) exceeds required limit.
20. Suspension System • Air leak in air suspension system. • Broken spring leaf. • Suspension fastener is loose, missing or broken.	• Damaged, deflated air bag. • Cracked or broken main spring leaf or more than one broken spring leaf. • Part of spring leaf or suspension is missing, shifted out of place or in contact with another vehicle component. • Loose U-bolt.
21. Tires • Damaged tread or sidewall of tire. • Tire leaking.	• Flat tire. • Tire tread depth is less than wear limit. • Tire is in contact with another tire or any vehicle component other than mud-flap. • Tire is marked "Not for highway use". • Tire has exposed cords in the tread or outer side wall area
22. Wheels, Hubs and Fasteners • Hub oil below minimum level. (When fitted with sight glass.) • Leaking wheel seal.	• Wheel has loose, missing or ineffective fastener. • Damaged, cracked or broken wheel, rim or attaching part. • Evidence of imminent wheel, hub or bearing failure.
23. Windshield Wiper/Washer • Control or system malfunction. • Wiper blade damaged, missing or fails to adequately clear driver's field of vision.	<i>When necessary for prevailing weather condition.</i> • Wiper or washer fails to adequately clear driver's field of vision in area swept by driver's side wiper.